

# SAFETY DATA SHEET



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

### 1.1 Product identifier

**Product name** PROSTRENGTH RAPID SET CONCRETE  
**Synonyms** PROSTRENGTH • RAPID SET CONCRETE

### 1.2 Uses and uses advised against

**Uses** CEMENT PRODUCTION

### 1.3 Details of the supplier of the product

**Supplier name** CEMENT AUSTRALIA PTY LIMITED  
**Address** 18 Station Ave, Darra, QLD, 4076, AUSTRALIA  
**Telephone** (07) 3335 3000; 1300 236 368  
**Fax** (07) 3335 3000; 1800 236 368  
**Email** [ca.compliance@cemaust.com.au](mailto:ca.compliance@cemaust.com.au)  
**Website** <http://www.cementaustralia.com.au>

### 1.4 Emergency telephone numbers

**Emergency** (07) 3335 3000; 1300 236 368 (Business Hours)  
**Emergency** 13 11 26 (After Hours)

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

#### Physical Hazards

Not classified as a Physical Hazard

#### Health Hazards

Skin Corrosion / Irritation: Category 2  
Serious Eye Damage / Eye Irritation: Category 1  
Specific Target Organ Toxicity (Single Exposure): Category 3 (Respiratory Irritation)  
Specific Target Organ Toxicity (Repeated Exposure): Category 2

#### Environmental Hazards

Not classified as an Environmental Hazard

### 2.2 GHS Label elements

**Signal word** DANGER

#### Pictograms



#### Hazard statements

H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.

## PRODUCT NAME PROSTRENGTH RAPID SET CONCRETE

### Prevention statements

|      |                                                                                               |
|------|-----------------------------------------------------------------------------------------------|
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray.                                              |
| P264 | Wash thoroughly after handling.                                                               |
| P271 | Use only outdoors or in a well-ventilated area.                                               |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |

### Response statements

|                    |                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------|
| P302 + P352        | IF ON SKIN: Wash with plenty of water.                                                                                           |
| P304 + P340        | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                                                       |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310               | Immediately call a POISON CENTRE or doctor/physician.                                                                            |
| P314               | Get medical advice/attention if you feel unwell.                                                                                 |
| P321               | Specific treatment is advised - see first aid instructions.                                                                      |
| P362 + P364        | Take off contaminated clothing and wash it before reuse.                                                                         |

### Storage statements

|             |                                                                  |
|-------------|------------------------------------------------------------------|
| P403 + P233 | Store in a well-ventilated place. Keep container tightly closed. |
| P405        | Store locked up.                                                 |

### Disposal statements

|      |                                                                        |
|------|------------------------------------------------------------------------|
| P501 | Dispose of contents/container in accordance with relevant regulations. |
|------|------------------------------------------------------------------------|

### 2.3 Other hazards

Some susceptible individuals may exhibit an allergic skin response upon exposure to Portland Cement, possibly due to trace amounts of chromium.

Prolonged exposure to Portland Cement in the wet form can cause serious, potentially irreversible skin or eye damage in the form of chemical burns. The same serious injury can occur if wet or moist skin or eyes have prolonged contact exposure to dry Portland Cement.

Dust created when the cured product is cut, grinded or machined may contain crystalline silica, some of which may be respirable. Repeated exposure to respirable crystalline silica dust may cause lung fibrosis (silicosis) and lung cancer.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

| Ingredient                  | CAS Number | EC Number | Content   |
|-----------------------------|------------|-----------|-----------|
| QUARTZ (CRYSTALLINE SILICA) | 14808-60-7 | 238-878-4 | <40%      |
| PORTLAND CEMENT             | 65997-15-1 | 266-043-4 | <30%      |
| CALCIUM COMPOUND(S)         | -          | -         | <5%       |
| HEXAVALENT CHROMIUM         | 18540-29-9 | 606-053-1 | <0.001%   |
| WASHED AGGREGATE            | -          | -         | 30 to 50% |

**Ingredient Notes** Depending upon the source material, may contain varying amounts of respirable quartz (crystalline silica).

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

|                             |                                                                                                                                                                                                          |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye</b>                  | If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.                 |
| <b>Inhalation</b>           | If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.                                                                                                                |
| <b>Skin</b>                 | If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor. |
| <b>Ingestion</b>            | For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Rinse mouth out with water and give plenty of water to drink. |
| <b>First aid facilities</b> | Eye wash facilities and safety shower should be available.                                                                                                                                               |

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to the eyes, skin and respiratory system. Chronic over exposure to silica quartz dust may result in silicosis (lung disease). Principal symptoms of silicosis are coughing and breathlessness. Some individuals may exhibit an allergic response upon exposure to this product, possibly due to the trace amounts of chromium present. Crystalline silica and hexavalent chromium compounds are classified as carcinogenic to humans (IARC Group 1).

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Use an extinguishing agent suitable for the surrounding fire.

**5.2 Special hazards arising from the substance or mixture**

Non flammable. May evolve toxic gases if strongly heated.

**5.3 Advice for firefighters**

No fire or explosion hazard exists.

**5.4 Hazchem code**

None allocated.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then collect and place in suitable containers for reuse or disposal. Avoid generating dust.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store in a cool, dry, well ventilated area, removed from moisture, incompatible substances and foodstuffs. Ensure packages are adequately labelled, protected from physical damage and sealed when not in use.

**7.3 Specific end uses**

Processing of this product may result in more than 1% crystalline silica and, therefore, is considered a Crystalline Silica Substance in accordance with the Safe Work Australia Model Code of Practice: Managing risks of respirable crystalline silica in the workplace. This product should be used in accordance with this Code of Practice and the requirements of the WHS Regulator.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**8.1 Control parameters****Exposure standards**

| Ingredient                                      | Reference      | TWA |                   | STEL |                   |
|-------------------------------------------------|----------------|-----|-------------------|------|-------------------|
|                                                 |                | ppm | mg/m <sup>3</sup> | ppm  | mg/m <sup>3</sup> |
| Chromium (VI) compounds (as Cr)                 | SWA [AUS]      | --  | 0.05              | --   | --                |
| Portland cement                                 | SWA [AUS]      | --  | 10                | --   | --                |
| Portland cement (respirable dust)               | SWA [Proposed] | --  | 1                 | --   | --                |
| Quartz (respirable dust)                        | SWA [AUS]      | --  | 0.05              | --   | --                |
| Quartz (respirable dust)                        | SWA [Proposed] | --  | 0.05              | --   | --                |
| Quartz (respirable dust) (Precautionary advice) | WorkSafe VIC   | --  | 0.02              | --   | --                |

## Biological limits

| Ingredient          | Reference      | Determinant             | Sampling Time                   | BEI                                      |
|---------------------|----------------|-------------------------|---------------------------------|------------------------------------------|
| HEXAVALENT CHROMIUM | ACGIH BEI      | Total chromium in urine | End of shift at end of workweek | 25 µg/L                                  |
|                     | ACGIH BEI      | Total chromium in urine | Increase during shift           | 10 µg/L                                  |
|                     | WEL [UK]       | Total chromium in urine | Post shift                      | 10 µmol chromium/mol creatinine in urine |
|                     | WES [NZ]       | Total chromium in urine | End of shift at end of workweek | 30 µg/L                                  |
|                     | WES [Proposed] | Total chromium in urine | End of shift at end of workweek | 25 µg/L                                  |

## 8.2 Exposure controls

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

## PPE

|                    |                                                                                                                                                                                                                                |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye / Face</b>  | Wear dust-proof goggles.                                                                                                                                                                                                       |
| <b>Hands</b>       | Wear PVC or rubber gloves.                                                                                                                                                                                                     |
| <b>Body</b>        | When using large quantities or where heavy contamination is likely, wear coveralls.                                                                                                                                            |
| <b>Respiratory</b> | Where an inhalation risk exists, wear a Class P2 (particulate) / N95 respirator. At high dust levels, wear an Air-line / Full Facepiece Supplied-Air Respirator (SAR) or a Full-face Class P3 (particulate) / N100 respirator. |



# 9. PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

|                           |                  |
|---------------------------|------------------|
| Appearance                | GREY POWDER      |
| Odour                     | ODOURLESS        |
| Flammability              | NON FLAMMABLE    |
| Flash point               | NOT RELEVANT     |
| Boiling point             | NOT AVAILABLE    |
| Melting point             | > 1200°C         |
| Evaporation rate          | NOT AVAILABLE    |
| pH                        | > 11 (solution)  |
| Vapour density            | NOT AVAILABLE    |
| Relative density          | 2.7 to 2.9       |
| Solubility (water)        | SLIGHTLY SOLUBLE |
| Vapour pressure           | NOT AVAILABLE    |
| Upper explosion limit     | NOT RELEVANT     |
| Lower explosion limit     | NOT RELEVANT     |
| Partition coefficient     | NOT AVAILABLE    |
| Autoignition temperature  | NOT AVAILABLE    |
| Decomposition temperature | NOT AVAILABLE    |
| Viscosity                 | NOT AVAILABLE    |
| Explosive properties      | NOT AVAILABLE    |
| Oxidising properties      | NOT AVAILABLE    |
| Odour threshold           | NOT AVAILABLE    |

## 9.2 Other information

|               |                                                                          |
|---------------|--------------------------------------------------------------------------|
| Particle Size | Up to 50% of the fresh dry material may be respirable (below 10 microns) |
|---------------|--------------------------------------------------------------------------|

# 10. STABILITY AND REACTIVITY

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation is not expected to occur.

**10.4 Conditions to avoid**

Avoid heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), ethanol, acids (e.g. hydrofluoric acid) and interhalogens (e.g. chlorine trifluoride). Water contact may increase product temperature 2°C to 3°C.

**10.6 Hazardous decomposition products**

May evolve toxic gases if heated to decomposition.

---

**11. TOXICOLOGICAL INFORMATION**

---

**11.1 Information on toxicological effects**

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Acute toxicity</b>           | Acute oral exposure may result in irritation of the mouth, throat, oesophagus and gastrointestinal tract.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Skin</b>                     | Irritating to the skin. Contact with powder or wetted form may result in irritation, rash and dermatitis.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Eye</b>                      | Contact with moisture in the eyes may result in irritation, lacrimation, pain, redness, conjunctivitis and possible alkaline burns aided by mechanical irritation and abrasion.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Sensitisation</b>            | Exposure to portland cement may trigger an allergic response, potentially due to trace amounts of chromium. This is more likely in individuals who are frequently exposed or have pre-existing skin sensitivities or allergies.                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Mutagenicity</b>             | Insufficient data available to classify as a mutagen.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Carcinogenicity</b>          | This product contains crystalline silica and trace amounts of hexavalent chromium compounds which are classified as carcinogenic to humans (IARC Group 1). However, there is sufficient information to conclude that the relative risk of lung cancer from exposure to crystalline silica is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.                                                                                                                                                                                                                                                                               |
| <b>Reproductive</b>             | Insufficient data available to classify as a reproductive toxin.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>STOT - single exposure</b>   | Irritating to the respiratory system. Over exposure may result in irritation of the nose and throat, with coughing. High level exposure may result in breathing difficulties.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>STOT - repeated exposure</b> | Repeated exposure to respirable silica may result in pulmonary fibrosis (silicosis). Silicosis is a fibronodular lung disease caused by deposition in the lungs of fine respirable particles of crystalline silica. Principal symptoms of silicosis are coughing and breathlessness. In the wet state, the likelihood of an inhalation hazard is reduced. Adverse health effects, usually associated with long term exposure to high crystalline silica dust levels are not anticipated due to the product form. However, the product may present a hazard if respirable quartz dust is generated (ie. sanding dried product). Repeated exposure to dust may cause lung fibrosis (silicosis). |
| <b>Aspiration</b>               | This product is a solid and aspiration hazards are not expected to occur.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

---

**12. ECOLOGICAL INFORMATION**

---

**12.1 Toxicity**

Due to the high pH of Portland cement when mixed with water, it can increase the pH of waterways, potentially leading to adverse effects on aquatic life. However, once cured and hardened into solid concrete, Portland cement is considered non-toxic to aquatic organisms.

**12.2 Persistence and degradability**

Product is persistent and would have a low degradability.

**12.3 Bioaccumulative potential**

Not expected to bioaccumulate.

**12.4 Mobility in soil**

The product hardens to a solid immobile substance. The product is not volatile but may be spread by dust-raising handling. A low mobility would be expected in a landfill situation.

### **12.5 Other adverse effects**

Avoid contamination of drains and waterways.

## **13. DISPOSAL CONSIDERATIONS**

### **13.1 Waste treatment methods**

**Waste disposal** Reuse or recycle where possible. Alternatively, ensure product is covered with moist soil to prevent dust generation and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information (if required).

**Legislation** Dispose of in accordance with relevant local legislation.

## **14. TRANSPORT INFORMATION**

**NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA**

|                                    | LAND TRANSPORT (ADG) | SEA TRANSPORT (IMDG / IMO) | AIR TRANSPORT (IATA / ICAO) |
|------------------------------------|----------------------|----------------------------|-----------------------------|
| <b>14.1 UN Number</b>              | None allocated.      | None allocated.            | None allocated.             |
| <b>14.2 Proper Shipping Name</b>   | None allocated.      | None allocated.            | None allocated.             |
| <b>14.3 Transport hazard class</b> | None allocated.      | None allocated.            | None allocated.             |
| <b>14.4 Packing Group</b>          | None allocated.      | None allocated.            | None allocated.             |

### **14.5 Environmental hazards**

Not a Marine Pollutant.

### **14.6 Special precautions for user**

**Hazchem code** None allocated.

## **15. REGULATORY INFORMATION**

### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications** Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings** **AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)**  
Some components are listed on AIIC, or are exempt.

## **16. OTHER INFORMATION**

**Additional information** Advice Note:  
Cement Australia believes the information in this document to be accurate as at the date of preparation, but, to the maximum extent permitted by law, Cement Australia accepts no responsibility for any loss or damage caused by any person acting or refraining from action because of this information. The provision of this information should not be construed by anyone as a recommendation to use this product. No one should use any product in violation of any patent or other intellectual proprietary rights or in breach of any statute or regulation. Users should rely on their own knowledge and inquiries and make their own determination as to the applicability of this information in relation to their particular purposes and specific circumstances. Each user should read this SDS and consider the information in the context of how the product will be handled and used in the workplace and in conjunction with other substances or products.

Manufacturing Plants  
Geelong: 292 Thompson Road, Geelong North VIC 3215  
Brisbane: 77 Pamela St, Pinkenba QLD 4008  
Auburn: Highgate Street, Auburn NSW 2144  
Townsville: Benwell Road, Townsville QLD 4810

**CEMENT CONTACT DERMATITIS:** Individuals using wet cement, mortar, grout or concrete could be at risk of developing cement dermatitis. Symptoms of exposure include itchy, tender, swollen, hot, cracked or blistering skin with the potential for sensitisation. The dermatitis is due to the presence of soluble (hexavalent) chromium.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

|                   |                                                                                                 |
|-------------------|-------------------------------------------------------------------------------------------------|
| ACGIH             | American Conference of Governmental Industrial Hygienists                                       |
| CAS #             | Chemical Abstract Service number - used to uniquely identify chemical compounds                 |
| CNS               | Central Nervous System                                                                          |
| EC No.            | EC No - European Community Number                                                               |
| EMS               | Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)                   |
| GHS               | Globally Harmonized System                                                                      |
| GTEPG             | Group Text Emergency Procedure Guide                                                            |
| IARC              | International Agency for Research on Cancer                                                     |
| LC50              | Lethal Concentration, 50% / Median Lethal Concentration                                         |
| LD50              | Lethal Dose, 50% / Median Lethal Dose                                                           |
| mg/m <sup>3</sup> | Milligrams per Cubic Metre                                                                      |
| OEL               | Occupational Exposure Limit                                                                     |
| pH                | relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline). |
| ppm               | Parts Per Million                                                                               |
| STEL              | Short-Term Exposure Limit                                                                       |
| STOT-RE           | Specific target organ toxicity (repeated exposure)                                              |
| STOT-SE           | Specific target organ toxicity (single exposure)                                                |
| SUSMP             | Standard for the Uniform Scheduling of Medicines and Poisons                                    |
| SWA               | Safe Work Australia                                                                             |
| TLV               | Threshold Limit Value                                                                           |
| TWA               | Time Weighted Average                                                                           |

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**PRODUCT NAME    PROSTRENGTH RAPID SET CONCRETE**

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmtglobal.com](mailto:info@rmtglobal.com)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**