



CONSISTENTLY
BRIGHT



WHITE CEMENT


Blends with raw materials to suit your project
White cement for decorative finishes
Add oxide for a coloured finish
Conforms to AS3972

WHITE CEMENT

- ✓ Blends with raw materials to suit your project
- ✓ Compatible with render and mortar plasticisers
- ✓ Add oxide for a deeper, coloured finish
- ✓ Conforms to AS3972

cementaustralia.com.au or call 1300 CEMENT (1300 236 368)

**CEMENT
AUSTRALIA®**



GROUT



CONCRETE



MORTAR



RENDER

Cement Australia's White Cement can be used with additives and supplementary cementitious materials*; it is versatile across a large number of applications.

- ✓ Portland White Cement - easy to batch, mix, lay, rake or iron
- ✓ Suitable for additive addition including Hydrated Lime, Clay, Brickies Own
- ✓ Quality product tested by Cement Australia's NATA accredited laboratory and backed with our national technical support
- ✓ Flexible and easy ordering alongside your other Cement Australia products
- ✓ High Early strength attainment
- ✓ **20% less GP cement is required to batch M3 Mortar and 25% less GP Cement for M4 Mortar**

SUGGESTED MIX RATIOS

APPLICATION	CEMENT	SAND	AGGREGATE
Concrete – General Purpose	1	2	3
M3 Mortar	1	5	-
M3 Mortar – Enhanced Workability	1	6 +1 Hydrated Lime	-
M4 Mortar	1	4	-
Render	1	3	-

**Please note: Colour results may vary - the colour of the finished product may vary due to natural differences in raw materials. Any supplementary cementitious materials added can affect the resulting mortar or concrete colour.*

PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

DIRECTIONS FOR USE

1. Combine cement, clean aggregate and sand in correct proportion in a non-porous vessel. Large jobs require a concrete mixer. Add a Cement Australia oxide to colour your project. Note: For a whiter finish, select 'white' sand.
2. Add clean water gradually and mix thoroughly. Use enough water to make a workable mix. Excess water ruins good concrete.
3. Use the product immediately after mixing. Keep moist for 7 days for the best results.

HINTS and TIPS

Admixtures such as air entrainers, thickening agents or plasticisers can be used but should always be used in accordance with the manufacturers' recommendations.

Where specific colour or other properties are required, a trial with the available materials should be undertaken before completing the actual job.

Item Code 14026

Cement Australia

White Cement 20kg



9 311808 021533